



PB-1 – Polyester braided push back sleeving

Item description	Expandable braided sleeve made of a Polyester Yarn monofilament. The main characteristic is its property to expand when pressed till almost double of the original diameter and come back to the original one if released.		
	The expandable structure is extremely useful for its property to adapt to cables, harness		

Tensile strenght	23 N				
Melting point	256°C				
Softening point	210°C				
Working temperature	125°C				
Flammability	flame retardant VW-1				
Thermal aging 158 h a 168°C	Tensile strenght is 80% of the original value				
Other	Good resistance to mechanical solicitations, liquids, solvents and mold. The polyester yarn resists to water and humidity. PB-1 is Halogen Free.				
	Diameters r	ange			
Original Diameter	May Diameter	Formation	Speel packing mt		

Diameters range					
Original Diameter	Max Diameter	Formation	Spool packing mt.		
3	6	16x3	800		
4	8	24x3	600		
5	10	24x3	600		
6	12	32x3	400		
8	15	40x3	400		
10	18	48x3	300		
12	22	56x3	300		
15	25	64x3	300		
20	30	72x3	300		
25	38	96x3	200		
30	49	120x3	100		
40	64	120x4	100		
50	70	120x5	100		

It must be stored in a dry place, inside plastic bags, away from direct sunlight, weathering, chemical materials, direct heat sources or fire. Storage time is 12 months.

The values given above are believed to be accurate and given as a matter of information only. As usage conditions are beyond our control we suggest the customer to confirm values and product compatibility prior to its use. We don't guarantee nor accept any responsibility for any particular usage.

